

# FireWall Valve LLC

For Fire Protection Valves

[Home](#)

[ABOUT](#)

[UL/FM Fire Protection](#)

[Plumbing Valves](#)

[CONTACT US](#)

## White PVC Ball Valve, Model FW300

- 150 PSI @ 73 Deg. F.
- White Color
- NSF Approved
- Fits Sch. 40 & Sch. 80 Pipe
- Threaded or Solvent Ends
- Threaded Ends Comply With ASTM B1.20.1
- Solvent Ends Comply With ASTM D2466
- Sizes 1/2" - 4"



## White PVC Ball Valve- Economy Pattern, Model FW301

- 150 PSI @ 73 Deg. F.
- Economy Pattern
- White Color
- Santoprene Seat Seals
- Fits Sch. 40 & Sch. 80 Pipe
- Threaded or Solvent Ends
- Sizes 1/2" - 4" & 6"



## PVC Ball Valve - Sch. 80, Model FW303

- 150 PSI @ 73 Deg. F.
- Gray Color
- Sch. 80
- NSF Approved
- Fits Sch. 40 & Sch. 80 Pipe
- Threaded or Solvent Ends
- Threaded Ends Comply With ANSI B1.20.1
- Solvent Ends Comply With ASTM D2466
- Sizes 1/2" - 4"



## PVC Ball Valve- Single Union, Model FW304

- Single Union
- 150 PSI @ 73 Deg. F.
- White Color
- EPDM Seat Seals & "O" Rings
- Full Port Ball
- Threaded or Solvent Ends
- Sizes 1 1/2" & 2"



## PVC Ball Valve- True Union - Solvent & Threaded, Model FW305

- Full Port Ball
- True Union
- 150 PSI @ 73 Deg. F.

- Gray Color
- Sch. 80 PVC Body
- PTFE Seat Seals
- EPDM "O" Ring
- Supplied with Both Threaded & Solvent Ends
- Threaded Ends Comply with NPT ANSI B2.1
- Solvent Ends Comply with ASTM D2467
- Unique Double Union / Double Block Design
- External Adjustment for Seat Wear
- Sizes 1/2" - 2"



### PVC Ball Valve - True Union - Solvent or Threaded, Model FW306

- Full Port Ball
- True Union
- 150 PSI @ 73 Deg. F.
- Gray Color
- Sch. 80 PVC Body
- PTFE Seat Seals
- EPDM "O" Ring
- Specify Either Solvent or Threaded Ends
- Unique Double Union / Double Block Design
- External Adjustment for Seat Wear
- Sizes 2-1/2" - 4"



### CPVC Ball Valve - PTFE Seats, Model FW307

- CPVC
- 100 PSI @ 180 Deg. F.
- NSF Approved
- White Color
- PTFE Seat Seals
- EPDM "O" Ring
- Solvent Ends Comply with ASTM D2846
- Sizes 1/2" - 2"

