

FireWall Valve LLC

For Fire Protection Valves

[Home](#)

[ABOUT](#)

[UL/FM Fire Protection](#)

[Plumbing Valves](#)

[CONTACT US](#)

UL/FM Alarm Check Valves - Model F - 250 PSI-Wet System Valves - Water Motor Alarm

Ductile Iron material to ASTM - A536
Flanged x Flanged, Grooved x Grooved and
Grooved x Flanged available
Rated for maximum 17.5 Bar (250 PSI) operating
pressure
Size: 3", 4", 6", 8"
Variable Pressure Trim with Retard Chamber and
Water Motor Gong
Constant Pressure Trim available as an option
Epoxy painted internally & externally
UL Listed and FM Approved



UL/FM Water Motor Alarm Gong

Hydraulically operated mechanical bell used
along with fire protection system valves
Corrosion resistant Aluminium alloy material,
epoxy coated all over
Wall mounted or direct online mounting type
UL Listed and FM Approved



UL/FM Retard Chamber For Variable Pressure Wet Pipe Sprinkler Systems 250 PSI

Retard Chamber is a surge tank that reduces the possibility of false
alarms due to water supply pressure surges.
It has a high-strength, ductile iron body and is designed for use Alarm
Check Valves
The body is painted inside and outside for increased corrosion
Resistance.
UL Listed and FM Approved

